

Professional, water- and moisture-resistant, mass-tinted, polymer calendered film.



Technical specifications :

Thickness: 80 microns
Polymer Vinyl

Storage: -5°C to +40°C

Glossy appearance

Thermoformable: Slightly

Protective liner:
137 gr/m² siliconized PE paper

Durability: over 8 years outdoor

Temperature resistance: -40°C to +80°C

Usage exterior
Extreme climatic conditions
Opaque film (grey back)
Permanent
Easy to install
Water bonding
Dry bonding



Application:

Supports:
Glass, aluminum, metal, varnished wood, varnished glass or carbon fiber, paint, rigid plastic, automotive paint

Chemical resistance: Resistant to acids, alkalis and salts.

Excellent water resistance.

Application temperature: between 10 and 30°C



Advice from mpa pro :

We recommend wet application for stickers over 50cm.

Recommended application temperature: +20°C

Limit of use:

Wavy or highly irregular surfaces
Substrates that do not have a clean, smooth surface
Materials with low cohesion between paint and substrate
Stainless steel
Flexible supports
3-dimensional surfaces (e.g. balls, pyramids)

Not suitable for total vehicle covering

Will not stick to the following materials:

Leather
Unvarnished wood
Textile



Maintenance tip :

Soapy water solution

Installation video:

